

optris CS / CSmicro / CT series

CTex LT + CTex LT hot		Mechanical accessories		
OPTCTEX	ACCTFB / ACCTFBMH / ACCTFB2	ACCTTAS	ACCTKF40GE / ACCT-KF40B270 / ACCTKF40SI	
Aluminum housing with mounting device to accommodate the Zener barriers (top-hot rail) and the CT electronics Advantage - Two-piece measuring system with active electronic for evaluation and passive IR receiver (sensing head) - CTex sensing head can be installed as passive element in hazardous areas - Energy limitation with appropriate zener barriers (STAHL) with approval for zone 1 (PTB 01 ATEX 2053/ E II (1/2) GD [EEEx ia/Ib] IIC/IIB) 	Mounting bracket, adjustable in one axis (M12x1 sensing head, massive housing, mounting of CT sensing head + Laser-Sightingtool) 	Tilt assembly for heads with optical resolution $\geq 10:1$ 	KF40 flange for CTLT with Ge window, for CT1M, 2M, 3M with B270 window, for CT4M with Si window (up to 10-7 mbar) 	
	ACCTRAIL Rail mount adapter for CT electronics 	ACCTMB Mounting bolt with thread M12x1 	ACCTMG Mounting fork, adjustable in 2 axes, with thread M12x1 	

Optical accessories		
ACCTCF / ACCTPW	ACCTCFE / ACCTPWE	D08ACCTLST / ACCTOEMLST
CF-lens or protective window (for LT) for M12x1 sensing head ACCTCFHT / ACCTPWHT for 1M, 2M, 3M ACCTPWSI35M for 4M 	CF-lens or protective window (for LT) with external thread for air purge or massive housing ACCTCFHTE / ACCTPWHTe for 1M, 2M, 3M ACCTPWSI35ME for 4M 	Laser-Sightingtool (for CT) OEM Laser-Sightingtool, 635 nm, rotation symmetrical, for connection to CT electronics, power supply via CT electronic box or battery 
ACCTRAM Right angle mirror for measurements 90° to the sensor axis for sensing heads with optical resolution $\geq 10:1$ 	ACCTPA + ACCTST20 (20 mm length) / ACCTST40 (40 mm length) / ACCTST88 (88 mm length) Pipe adapter with M12x1 internal thread - Sighting tube with M12x1 external thread 	

Air purges and protective housings

ACCSAP	ACCTAPMH	Massive housing of:	
Air purge collar (for heads with optical resolution $\geq 10:1$)	Air purge collar for Massive housing (D06) / CSmicro H5 / CThot / CT P3 / CT P7	- stainless steel (D06ACCTMH5) - compact, brass (D06ACCTMHB) - anodized aluminium (D06ACCTMHA)	- stainless steel version with CF optics (D06ACCTMHSCF) - stainless steel version for HT CF optics (D06ACCTMHSCFHT)
			
ACCTAPLCFHT	ACCTAPL	ACCTAP / ACCTAP2 (2:1 optics)	
Air purge collar, laminar, with integrated CF lens (for 1M / 2M / 3M)	Air purge collar, laminar	Air purge for CT heads (not for heads with 32 mm length)	
			

Combinations

ACCTAPL	ACCTMG		ACCTFB2	D06ACCTLISTIACTOEMIST	
Air purge collar, laminar	Mounting fork	Device adjustable in two axes	Mounting bracket for sensing head + Sighting tool	OEM Laser-Sightingtool	Sensing head with Laser-Sighting tool
					
ACCTFB	ACCTMB	ACCTAB	D06ACCTAPMH	ACCTAPMH	
Mounting bracket for M12x1 sensing head	Mounting bolt	Device-adjustable in two axes	Massive housing, stainless steel	Airpurge, stainless steel	Massive housing with air purge
					